WHAT IS CLAIMED IS:

1. A method for designing a logic circuit comprising:

maintaining a data structure representative of a model, the model including combinational blocks, state elements and graphical library elements of the logic circuit; and

generating an architectural model and an implementation model from the data structure.

2. The method of claim 1 wherein the data structure comprises a description of a net list.

3. The method of claim 2 wherein the data structure comprises:

elements representing logical functions;

elements representing connection points to gates;

elements representing all bits of a simulation state; and

elements representing an arbitrary collection of bits within the simulation state.

4. The method of claim 4 wherein the elements are all C++ classes.

5. The method of claim 1 wherein the architectural model comprises C++ software code.

6. The method of claim 1 wherein the implementation model comprises Hardware Design Language (HDL).

7. The method of claim 6 wherein the HDL is Verilog.

8. The method of claim 6 wherein the HDL is Very high speed integrated circuit Hardware Design Language (VHDL).

9. A method comprising:

specifying a model containing combinatorial blocks, state elements and graphical library elements;

maintaining a descriptive net list of the model; and

generating a C++ model and a Verilog model from the descriptive net list.

10. The method of claim 9 further comprising displaying the model on a graphical user interface (GUI).

11. The method of claim 9 wherein the net list comprises gates, nodes and nets.

12. The method of claim 9 wherein maintaining comprises parsing and analyzing the combinatorial blocks, state elements and graphical library elements of the model.

13. The method of claim 9 wherein generating comprises:
partitioning a topology of the net list into a plurality of partitions; and
code ordering each of the partitions.

14. A computer program product residing on a computer readable medium having instructions stored thereon which, when executed by the processor, cause the processor to:

specify a model containing combinatorial blocks, state elements and graphical library elements;

maintain a descriptive net list of the model; and

generate a C++ model and a Verilog model from the descriptive net list.

15. The computer product of claim 14 wherein the computer readable medium is a random access memory (RAM).

16. The computer product of claim 14 wherein the computer readable medium is a read only memory (ROM).

17. The computer product of claim 14 wherein the computer readable medium is a hard disk drive.

18. A processor and memory configured to:

specify a model containing combinatorial blocks, state elements and graphical library elements;

maintain a descriptive net list of the model; and

generate a C++ model and a Verilog model from the descriptive net list.

19. The processor and memory of claim 18 wherein the processor and memory are incorporated into a personal computer.

20. The processor and memory of claim 18 wherein the processor and memory are incorporated into a network server residing in the Internet.

21. The processor and memory of claim 18 wherein the processor and memory are incorporated into a single board computer.

22. A system comprising:

a graphic user interface (GUI) for receiving parameters from a user to generate a model and displaying the model, the model containing combinatorial blocks, state elements and graphical library elements;

a maintenance process to manage a data structure representing a descriptive net list of the model; and

a code generation process to generate a C++ model and a Verilog model from the data structure.

23. The system of claim 22 wherein the data structure comprises gates, nodes and nets.

24. The system of claim 22 wherein the maintenance process comprises parsing and analyzing the combinatorial blocks, state elements and graphical library elements of the model.

25. The system of claim 22 wherein the code generation process comprises:

partitioning a topology of the net list into a plurality of partitions; and

code ordering each of the partitions.

26. A data structure comprising:

elements representing logical functions of a logic model;

elements representing connection points to gates of the logic model;

elements representing all bits of a simulation state of the logic model; and

elements representing an arbitrary collection of bits within the simulation state of the logic model.

27. The data structure of claim 26 wherein the elements are stored in a binary tree.

28. The data structure of claim 26 wherein the elements are stored in a linked list.